

## AP4C-VB

### COMBINED CHEMICAL AND BIOLOGICAL THREATS DETECTOR

The AP4C-VB is a unique, ready-to-mount system for vehicles, shelters, and critical infrastructure, designed to provide early warning of combined chemical and biological threats. Its compact and rugged design enables continuous monitoring of airborne agents in the environment, ensuring fast and reliable detection.

Thanks to its advanced core detection technology, the AP4C-VB is ideal for use either as an independent detector for infrastructure protection or as an integrated solution within vehicles and combat systems. Its machine learning based alarm algorithm enables real-time adaptation to complex variations in both outdoor and indoor environments, ensuring a fast and low-regret response. The system features an open communication protocol, allowing seamless integration into any CBRN defense architecture



#### KEY FEATURES & BENEFITS

- Dual chemical-biological sensor
- Continuous & simultaneous monitoring
- Universal detection of airborne threats
- Versatile adaptability across diverse environments
- Immune to common interferences & no false alarms
- Easy and flexible system integration
- Minimal maintenance requirements

#### IDEAL FOR

- Military vehicles
- CBRN vehicles
- Shelters
- VIP conferences
- Public events
- Critical Infrastructure

# AP4C-VB

## COMBINED CHEMICAL AND BIOLOGICAL THREATS DETECTOR

### SPECIFICATIONS<sup>1</sup>

<b>Dimensions:</b>	342 x 218.4 x 170 mm / 13.5 x 8.6 x 6.7 inch
<b>Weight:</b>	~4.9kg (10.8 lbs) with 2 x hydrogen cylinders
<b>Sensing Technology:</b>	Hydrogen Flame Spectrometry (FPD)
<b>Chemical Detection Performance:</b>	CWA (including 4th generation), TIC & TIM in the form of Gas, Vapor and Aerosol. Sub µg/m <sup>3</sup> (ppb) range in few seconds.
<b>Biological Detection Performances</b>	BWA, biological materials and encapsulated threats (bacteria, viruses, toxins) Aerosols: 1 – 10 microns ≤100 ACPLA <sup>2</sup> in less than 60 seconds.
<b>Alarm Capabilities:</b>	Simultaneous Chem & Bio alarm mode Audible and Visual (External) Adjustable alarm settings by the user
<b>Measurement Frequency:</b>	Real time continuous monitoring
<b>Operating Wind:</b>	Detect up to 110 km/h (68 mph) while in motion or fixed site.
<b>Storage Temperature:</b>	-39°C to +71°C / -38°F to +160°F
<b>Operating Temperature:</b>	-32°C to +50°C / -26°F to +122°F
<b>Operating Humidity:</b>	95% RH (non-condensing) @T49°C (120.2°F)
<b>Power Supply:</b>	24V DC
<b>H2 Running Time:</b>	Up to 24 hours with 2 hydrogen cylinders (room temperature)
<b>Connectivity:</b>	MIL Grade RS-485 and Ethernet Amphenol connector to a 3rd party solution or Proengin software solution
<b>Communication:</b>	MODBUS Protocol RTU and TCP
<b>Regulation/Performance Test:</b>	CE IP 65 MIL-STD-810-H MIL-STD-461-G MIL-STD-1275-F
<b>Warranty:</b>	1 year

<sup>1</sup> Specifications subject to change

<sup>2</sup> Tested under ACPLA equivalent conditions. Contact us for details

### ACCESSORIES & SERVICES

Prepaid maintenance and extended warranty options are available upon initial acquisition.

Take command of your CBRN responses thanks to Proengin fully modular and scalable systems offering.



Turn key system solutions



Bio Air Sampler

## Proengin

### FOR MORE INFORMATION:

WORLDWIDE  
contact@proengin.com

USA(only)  
contactusa@proengin.com



To maximise the value of Proengin's solutions, including white papers, webinars, training and more, visit Proengin Academy.

